Alcom-FT Technical Report Series
ALCOMFT-TR-01-168

ATTRIBUTE GRAMMARS AND AUTOMATIC COMPLEXITY ANALYSIS

MARNI MISHNA

Abstract. Attribute grammers provide a concise way to describe traits of a wide family of structures. Structures defined by context free grammars have been well studied by Delest, Fédou and more recently by Duchon. One of the principle benefits of this approach is the easy access to multivariate generating function equations from which average and higher moments are easily accessible. This work extends these notions to a wider class of structures and considers the application to algorithm analysis.

Résumé. Les grammaires attribuées permettent de décrire de façon concise propriétés de grandes familles de structures. En particulièr, les structures définies par une grammaire hors-contexte on été bien étudiées par Delest, Fédou et Duchon. Un des advantages principaux des grammaire attribuées est qu'elles donne des équations fonctionnelles des fonctions génératrices multivariées. De là, moyennes et autres moments sont aisément accessibles. Ce travail étend ces notions à une classe plus grande de grammaires: les structures décomposables. De plus, on montre ici comment les résultats obtenus peuvent être appliqués à l'analyse d'algorithmes.

1. Attribute Grammars

Attribute grammars were initially developed to give semantic interpretation to context-free grammars. Since their introduction by Knuth [9] they have made themselves useful in compilers and as a means of program description. The attribute value, or meaning, of a word can be viewed as the output of a function or program acting on the word. M. P. Delest and J.-M. Fédou [2] illustrated how attribute grammars are useful to the combinatorialist. This concept was further developed by I. Dutour and Fédou [3] who described a systematic approach to enumeration and random generation of object grammars, using attribute grammars to describe properties of the structures. Most recently Delest and P. Duchon[1] have given a characterization of those attributes which are well suited to certain types of manipulation.

This work considers a similar family of attributes extended over a larger class of structures. These structures are part of the Maple package `combstruct`, and so an implementation of many of the techniques is described. The main application described is algorithm analysis.

In this document, the suitable attributes are defined and further specified in the first two sections and the generating function consequences are considered in the third section. The fourth section introduces the Maple implementation and is followed by a comparison with the LUO system for automatic average case algorithm analysis developed by the Algorithms Project of INRIA [5, 10].

1.1. Grammars and Specifications.

The structures considered here are those described in detail in [5]. They are built from atoms of weight one (commonly expressed as Z), and o, ϵs of weight 0. The constructors are disjoint union $|$, cartesian product $\cdot$, sequence *, $\mathrm{Set}()$, $\mathrm{MultiSet}()$ and $\mathrm{Cycle}()$. These latter constructors form, respectively, sequences, sets without or with duplication and cycles of their arguments. They shall collectively be referred to as the iterative constructors. They admit simple cardinality restrictions: $\mathrm{card(inality)} \leq k$, $\mathrm{card} = k$ and $\mathrm{card} \geq k$, for any non-negative integer k.

Definition. Let $T = (T_1, T_2, \ldots, T_m)$ be an m-tuple of families of combinatorial objects. A *specification* is a rule $T_i = \Phi_i(T_1, T_2, \ldots, T_m)$ where Φ_i is ϵ, an atom or one of the aforementioned

This work has been partially supported by the IST Programme of the EU under contract number IST-1999-14186 ALCOM-FT.

Specification	Attribute definition		
$T = \epsilon \mid N \cdot T \cdot T$	$\text{size}(T)$	$=$	$0 \mid \text{size}(N) + \text{size}(T_1) + \text{size}(T_2)$
$(T_0 = \epsilon \mid N \cdot T_1 \cdot T_2)$	$\text{ipl}(T)$	$=$	$0 \mid \text{size}(T_1) + \text{size}(T_2) + \text{ipl}(T_1) + \text{ipl}(T_2)$
	$\text{numint}(T)$	$=$	$0 \mid 1 + \text{numint}(T_1) + \text{numint}(T_2)$
$N = Atom$	$\text{size}(N)$	$=$	1

FIGURE 1. Binary Trees and some attributes

constructors. A notion of derivation trees similar to context free grammar exists. Any structure which can be described in this way is *decomposable*, and a set of specifications is a *grammar*. If the atoms are labelled with the numeric labels, the grammar is labelled, otherwise it is unlabelled. A grammar is *well defined* if each specification generates a finite number of objects of each size, and uniquely so. The *size* of an object a, or $|a|$ is the number of atoms.

A wide variety of structures are decomposable. For example: plane binary trees ($T = \epsilon | Z \cdot T \cdot T$), non-plane trees ($T = Z \cdot \text{MultiSet}(T)$), permutations ($P = \text{MultiSet}(\text{Cycle}(Z, card > 0))$) and all structures definable with context-free grammars.

Definition. An *attribute* is a function which assigns a value to a structure. For example, the number of atoms is an attribute. An *attribute grammar* is a three-tuple (G, A, P) where G is a grammar, A is a set of attributes and P is a set of rules defining the value of attributes in A for structures in G. An attribute of a structure is *synthesized* if it is strictly a function of descendants of the derivation tree and it is *inherited* if it is a function of its ancestors.If the set of defining rules are formulated in such a way that all attributes can always be defined at each node of the derivation tree of each structure, then the grammar is *well defined*. Knuth [9] described an algorithm for determining this property of attribute grammars. If G is well defined, and A contains only synthesized attributes defined (possibly trivially) for each structure, the attribute grammar will be well defined.

The iterative constructors have at least two meaningful possibilities for an attribute. It may be defined as the sum of the values of the elements in the object, or as the value of a chosen element. The first is an *iterative* attribute and the second a *selective* attribute.

1.2. **Example: Binary Trees.** A binary tree is recursively defined as empty, or a node and two children trees, $T = \epsilon \mid N \cdot T \cdot T, N = Atom$. There are many recursively defined properties of trees that one may wish to study, such as the number of internal nodes (numint), or internal pathlength (ipl), the sum of distances from every node to the root. These can all be described by attributes, as is done in Figure 1.

1.3. **Linear Attributes.** A synthesized attribute of a structure defined by $T = \Phi(B_1, \ldots, B_k)$ is *linear* if it is a linear function of the attributes of the descendants. That is, it can be expressed as some function linear in $F_j(B_i)$ where $\{F_j\}$ is a set of attributes. An attribute grammar which consists only of linear attributes is aptly named a *linear attribute grammar*. In the example each of the attributes is linear. In the case where the grammar is context free, this corresponds to the notion of the *Q-comptable* grammars of Delest and Duchon.

2. Linear Attribute Specifications

The initial goal is to extract enumerative information about decomposable structures and their properties. In order to do so, we first limit our attention to a particular class of attributes: linear, synthesized. This section gives an explicit meaning to these terms for the given constructions.

Consider the explicit definition of linear attributes. Let $AG = (G, \{F_i\}, P)$ be an attribute grammar. Given a specification for a structure, the attribute depends on the operator. For example, the attribute value of a member in a union depends on the value of the union element from which it was derived. So, if $C = A \mid B$, the set of all possible values for $F_i(C)$ is a disjoint union of linear

combinations of attribute values of elements of A and linear combinations of attribute values of elements of B. This is written

$$F_i(C) = \gamma_i + \sum_{j=1}^{k} \alpha_{ij} F_j(A) \quad \Big| \quad \delta_i + \sum_{j=1}^{k} \beta_{ij} F_j(B),$$

where the $\gamma_i, \alpha_{ij}, \delta_i, \beta_{ij}$ are all integer constants.

Similarly, for products, a valid attribute operator for $C = A \cdot B$ is a linear combination of attributes of A and B. Thus, the range of attributes of $F_i(C)$ is

$$F_i(C) = \gamma_i + \sum_{j=1}^{k} \alpha_{ij} F_j(A) + \sum_{j=1}^{k} \beta_{ij} F_j(B).$$

This will also be written

$$F_i(C) = \gamma_i + \cdot(\sum_{j=1}^{k} \alpha_{ij} F_j(A) + \sum_{j=1}^{k} \beta_{ij} F_j(B)),$$

with a dot to facilitate notation readability.

Denote by Φ the iterative attribute which sums over all sub-elements of type Φ. That is, The iterative operator $A = \Phi(B)$ has a general form for a linear attribute of

$$F_i(A) = \Phi(\delta_i + \sum_{j=1}^{k} \alpha_{ij} F_j(B)) + \gamma_i.$$

In the case of sets, for example, this would have the interpretation that for each set $a \in A$,

$$F_i(a) = \gamma_i + \sum_{b \in a} \left(\delta_i + \sum_{j=1}^{k} \alpha_{ij} F_j(b)) \right).$$

The range of values of $F_i(A)$ is the set formed by considering all structures of type A and summing the value of the linear function over them.

With this notation the general specification of a structure is

$$A = \Phi_1(B_1^{(1)}, \ldots, B_{k_1}^{(1)}) | \ldots | \Phi_n(B_1^{(n)}, \ldots, B_{k_n}^{(n)}),$$

and an attribute of this specification has the general form:

$$F_i(A) = \bigcup_{m=1}^{n} \Phi_m(\delta_i^m + \sum_{j} \sum_{k=1}^{k_m} \alpha_{ij}^{(m,k)} F_j(B_k^{(m)})) + \gamma_i.$$

In this general expression Φ_i is a non union constructor and indexed, lower case greek letters indicate integer constants.

2.1. **Self-Referential Attributes.** It is notationally convenient at times for an attribute of a structure to be expressed in terms of another attribute of the structure itself. For example, the internal pathlength of the binary tree in Figure 1 could be rewritten with the rule $\mathrm{ipl}(T) = \mathrm{ipl}(T_1) + \mathrm{ipl}(T_2) + \mathrm{size}(T) - 1$. The reference to the size of the whole tree, $\mathrm{size}(T)$, is the self-reference. Even though T_1 and T_2 are both structures of type T, the attribute values $\mathrm{ipl}(T_1)$ and $\mathrm{ipl}(T_2)$ are not considered self-referential since T_1 and T_2 are descendants.

Grammars which are well defined with all self-references occurring outside of iterative attributes, have no greater expressive power than those without self-references since the attributes can be expressed strictly in terms of its descendants. An attribute grammar defined without any self-referential attributes is in *standard form*. The idea is akin to Knuth's observation that all inherited attributes can be rewritten as synthesized attributes.

Proposition 1. *Any linear, self-referential attribute in a well defined attribute grammar can be rewritten as a linear attribute in standard form.*

Proof. Let A be some decomposable structure and $\mathbf{F} = \{F_i\}_{i=1}^n$ be a set of attributes defined for A. Since the attribute grammar is well defined they all have values on A. Thus, there exists some total ordering of evaluation of $\mathbf{F}$, say $F_1', F_2', \ldots, F_n'$. The first in this total ordering must be either constant or depend on values of descendants. In either case all references to $F_1'(A)$ can be replaced by its value: either a constant or the value stated in terms of the descendants of A. This process can be iterated through the partial order until all attribute values of A are expressed in terms of descendants.

□

3. Generating Functions

Information about combinatorial structures can be conveniently encoded into ordinary and exponential generating functions. The name of the class doubles as the name of the generating function. For example, in the unlabelled case, $A(z) = \sum_{a \in A} z^{|a|} = \sum_{n>0} a_n z^n$ where a_n is the number of structures of size n. The labelled case is written $A(z) = \sum_{n>0} \frac{a_n z^n}{n!}$. A decomposable structure's generating function satisfies relations governed by the following folk theorem.

Theorem 2 (Folk theorem of combinatorial analysis)**.** *Given a specification for a class C, a set of equations for the corresponding generating functions is obtained automatically by the following translation rules. (The function ϕ is Euler's totient function.)*

Specification	$C(z)$	*Universe*
$C = A \mid B$	$A(z) + B(z)$	*either*
$C = A \cdot B$	$A(z)B(z)$	*either*
$C = A^*$	$\frac{1}{1-A(z)}$	*either*
$C = \mathrm{Set}(A)$	$\exp(A(z))$	*labelled*
$C = \mathrm{Cycle}(A)$	$\ln(\frac{1}{1-A(z)})$	*labelled*
$C = \mathrm{Set}(A)$	$\exp(\sum_{k>0}(-1)^{k-1}\frac{A(z^k)}{k})$	*unlabelled*
$C = \mathrm{Cycle}(A)$	$\sum_{k>0}\phi(k)/k \ln(\frac{1}{1-A(z^k)})$	*unlabelled*
$C = \mathrm{Multiset}(A)$	$\exp(\sum_{k>0}\frac{A(z^k)}{k})$	*unlabelled*

For specification $\Phi(B_1, \ldots, B_k)$ let $\mathcal{G}_\Phi(B_1, \ldots, B_k)$ denote the corresponding generating functions translation.

Multivariate generating functions are used to keep track of multiple properties; here, the value of attributes. The attribute generating function in an unlabelled universe with attributes $\{F_i\}$ is $A(z_1, z_2, ..., z_k) = \sum_{a \in A} z_1^{|a|} z_2^{F_2(a)} \cdots z_k^{F_k(a)}$, and in a labelled universe each term is divided by $|a|!$. By convention, the first parameter z_1 tracks size. This uses the fact that the grammar is well defined to ensure that the equations are meaningful. They satisfy very similar relationships as those in the folk theorem. This has been observed before with respect to additive attributes, and the relationships have been used before.

To describe this action, let $\alpha = [\alpha_{ij}]_{k \times k}$, and $\gamma = [\gamma_i]_{1 \times k}$ be matrices over some ring containing the range of values of attributes. If $\mathbf{z} = (z_1, \ldots, z_k)$, then denote $\mathbf{z}^\alpha = (z_1^{\alpha_{11}} \cdots z_k^{\alpha_{k1}}, \ldots, z_1^{\alpha_{1k}} \cdots z_k^{\alpha_{kk}})$ and $\mathbf{z}^\gamma = z_1^{\gamma_1} \cdots z_k^{\gamma_k}$.

Theorem 3. *Given the grammar specification*

$$A = \Phi_1(B_1^{(1)}, \ldots, B_{k_1}^{(1)}) \mid \ldots \mid \Phi_n(B_1^{(n)}, \ldots, B_{k_n}^{(n)})$$

where each Φ_i is a grammar constructor, and given the set of attributes

$$F_i(A) = \bigcup_{m=1}^{n} \Phi_m(\delta_i^{(m)} + \sum_j \sum_{k=1}^{k_m} \alpha_{ij}^{(m,k)} F_j(B_k^{(m)})) + \gamma_i^{(m)}$$

the multivariate generating function $A(\mathbf{z})$ satisfies

$$A(\mathbf{z}) = \sum_m \mathbf{z}^{\gamma^{(m)}} \mathcal{G}_{\Phi_m}(\mathbf{z}^{\delta^{(m)}} B_1^{(m)}(\mathbf{z}^{\alpha^{(m,1)}}), \ldots, \mathbf{z}^{\delta^{(m)}} B_{k_m}^{(m)}(\mathbf{z}^{\alpha^{(m,k_m)}})),$$

where $\mathcal{G}_{\Phi_m}$ is the generating function transformation based on the Theorem 2.

Proof. The result can be directly proved by a case by case analysis of each structure type. The general structure for such proofs is illustrated with the following proof of the unlabelled set transformation.

Here the statement is simplified to $A(\mathbf{z}) = \mathbf{z}^\gamma \mathcal{G}_{\mathrm{Set}}(\mathbf{z}^\delta B(\mathbf{z}^\alpha))$.

$$\begin{aligned}
A(\mathbf{z}) &= \sum_{a\in A} z_1^{F_1(a)} z_2^{F_2(a)} \ldots z_k^{F_k(a)} \\
&= \sum_{a\in A} \prod_{i=1}^{k} z_i^{\gamma_i + \sum_{b\in a}\delta_i + \sum_{j=1}^{k}\alpha_{ij}F_j(b)} \\
&= \mathbf{z}^\gamma \prod_{b\in B} (1 + \mathbf{z}^\delta \prod_{i=1}^{k} z_i^{\sum_{j=1}^{k}\alpha_{ij}F_j(b)}) \\
&= \mathbf{z}^\gamma \prod_{(e_1,e_2,\ldots,e_k)} (1 + \mathbf{z}^\delta \prod_{j=1}^{k} (\prod_{i=1}^{k} z_i^{\alpha_{ij}})^{e_j})^{N_B(e_1,e_2,\ldots,e_k)} \\
&= \mathbf{z}^\gamma \exp(\sum_{(e_1,\ldots,e_k)} N_B(e_1,\ldots,e_k) \ln(1 + \mathbf{z}^\delta \prod_{j=1}^{k} (\prod_{i=1}^{k} z_j^{\alpha_{ij}})^{e_j})) \\
&= \mathbf{z}^\gamma \exp(\sum_{k\geq 1} (-1)^{k+1} \frac{\mathbf{z}^{k\delta} B(\mathbf{z}^{k\alpha})}{k}) \\
&= \mathbf{z}^\gamma \mathcal{G}_{\mathrm{Set}}(\mathbf{z}^\delta B(\mathbf{z}^\alpha))
\end{aligned}$$

Here $N_B(e_1, ..., e_k)$ is the number of $b \in B$ that satisfy $F_i(b) = e_i$ for $i = 1, \ldots, k$. This is precisely the coefficient of $z_1^{e_1} \cdots z_k^{e_k}$ in the generating function of B.

□

3.1. **Example: Pathlength.** The generating function equations for binary tree with path length are consequences of the definitions. By applying the attribute grammar version of the folk theorem one has the equation $T(z,u) = 1 + z \cdot T(zu,u)^2$. Pathlength of labelled non-plane trees $P = Z \cdot \mathrm{Set}(P)$ is similar with $\mathrm{ipl}(P) = \mathrm{Set}(\mathrm{size}(P) + \mathrm{ipl}(P))$ leading to the equation $P(z,u) = z\exp(P(zu,u))$. These well known equations admit several interesting calculations, presented in the next section with the help of Maple.

Attributes can also be used to count occurrences of substructures. For example, the number of cycles in a permutation, described by the construction $P = \mathrm{Set}(\mathrm{Cycle}(Z))$ (labelled) is determined by the attribute grammar, $\{\mathrm{num}(P) = \mathrm{Set}(1)\}$ which yield $P(z,u) = z\exp(u\ln((1-z)^{-1}))$.

4. Maple Implementation

The main Maple package for combinatorial structure manipulation (combstruct) provides a template for the definition of attribute grammars.[1]

[1] A full description of the Maple library `algolib` which includes `combstruct`, and other generating function tools, is available at `http://algo.inria.fr`

4.1. **Grammar Syntax.** The attribute grammar syntax mirrors closely that of the `combstruct` grammars. This allows for maximal clarity and eliminates ambiguity. Now, Union, Prod, and the other `combstruct` operators act as functions to describe attributes. Further, self-referential attributes are permitted. Thus, if a grammar contains $A = B \mid C$, the attribute $F(A)$ in a corresponding attribute grammar is described

```
F(A)=Union(b_1*F_1(B)+...+b_k*F_k(B),c_1*F_1(C)+...+c_k*F_k(C))
                + a_1*F_1(A)+...+a_k*F_k(A)+a_0,
```

where the a_i, b_i and c_i are either integers or constants (names). Products are similar. Thus the set of valid attributes of `A=Set(B)` are written with syntax as follows,

```
F(A)=Set(b_1*F_1(B)+...+b_k*F_k(B)+b_0)+ a_1*F_1(A)+...+a_k*F_k(A)+a_0.
```

In the `combstruct` lexicon the constructor `Set` refers to multisets.

Since `combstruct` verifies that the original grammar is well defined, and since only linear, synthetic attributes are allowed, all attribute grammars in standard form are well defined. In the case of self-referential attributes, the program will ensure that the grammar is well defined and expand the self-references.

Those rules which are not explicitly defined are assigned recursive defaults. For example, together the specification $A = \text{Union}(B, C)$ and the attribute operator F invoke a default rule of $F(A) = \text{Union}(F(A), F(B))$. The default value of an atom is 1 and of an epsilon is 0. Thus, the default attribute is size.

4.2. **Example: Pathlength.** Using the generating function relationships for pathlength, and the existing Maple tools for manipulating generating functions, statistics for pathlength such as average, variance, and other moments are well within reach.

The binary tree grammar and the pathlength attribute grammar are expressed in Maple by

```
> sys := {B = Union(Epsilon, Prod(Node, B, B)), Node = Atom}:
> att:= {ipl(B) = Union(0, Prod(0, ipl(B)+size(B), ipl(B)+size(B)))}:
```

To determine the defining generating function equations, use the command `agfeqns`. The variable z marks the *size*, a default attribute.

```
> eqns:=  agfeqns(sys,att, unlabelled, [[u, ipl]], z);
```

$$\left\{B(z,u) = 1 + z\left(B(zu,u)\right)^2, Node(z,u) = z\right\}$$

The expression for average pathlength can be calculated from the number of trees on n nodes and the sum of all pathlengths on n nodes, or $[z^n]\frac{\partial}{\partial u}B(z,u) \mid_{u=1}$. Maple can solve for both of these quantities. The call to the function `equivalent`, also in `algolib` determines the asymptotic value of the generating function coefficients.

The function `agfmomentsolve` differentiates a given number n times with respect to each variable, sets the non-size variables to 1 and solves. When $n = 0$ this gives the size generating function. When $n = 1$ it solves for $\frac{\partial}{\partial u}B(z,u)|_{u=1}$ (returned as $B[2](z)$), the cumulative generating function for the attribute marked by u.

```
> agfmomentsolve(eqns, 0);
> num_trees:= equivalent(subs(%, B(z)), z, n);
```

$$\left\{Node(z) = z, B(z) = 1/2\,\frac{1-\sqrt{1-4\,z}}{z}\right\}$$

$$num_trees := \frac{4^n}{\sqrt{\pi}n^{3/2}} + O(\frac{4^n}{n^{5/2}})$$

```
> agfmomentsolve(eqns, 1):
> tot_pl:= equivalent(subs(%, B[2](z)), z, n);
> avg_pl:= gdev(tot_pl/num_trees, n=infinity,2);
```

$$tot_pl := 4^n + O(\frac{4^n}{\sqrt{n}})$$
$$avg_pl := \sqrt{\pi} n^{3/2} + O(n)$$

The variance is obtained from the next moment, $[x^n]\frac{\partial^2}{\partial u^2} B(z,u)|_{u=1}$. This system is also solvable. The asymptotic value of the coefficient is $(\frac{10}{3} - \pi)n^3 + O(n^{\frac{5}{2}})$.

5. Automatic Complexity Analysis

Historically attribute grammars have had a close connection with algorithm description. This property can be modified such that an attribute describes the number of steps (however that is defined) an algorithm requires when a given structure is input. Generating functions summarize this information and offer a means for automatic average case complexity analysis.

This idea has been explored in depth with respect to the decomposable structures defined here [4, 5, 10]. In fact, the system LUO is an implementation of this concept for a family of algorithms. The main drawback of this system is that only the final univariate generating functions are available.

Attribute grammars give relations for multivariate generating functions and hence for problems it can represent additional information such as variance and higher moments are available. Further, it may be possible to do a distribution analysis. As shall soon be demonstrated, the class of algorithms that attribute grammars can describe contains the LUO class, and further all solutions are obtainable from the attribute grammar generating function equations.

5.1. **LUO.** LUO in its original form, and as implemented in the `combstruct` package, allows the user to describe a class of algorithms using several simple programming primitives: sequence of programs, test on unions, partial program descent and full component iteration. A program $P(a : A)$ takes as input a decomposable structure type A defined in an accompanying grammar. The program is littered with counters. The cost of execution on input A is then calculated as the sum of the counters encountered in a run. The program returns $\tau P_A(z)$ and an asymptotic value for $[z^n]\tau P_A(z)$, the total cost of running $P(a : A)$ on all inputs of type A and size n. The average complexity is then $[z^n]\tau P_A(z)/[z^n]A(z)$.

5.2. **LUO vs Attribute Grammars.** There is a direct correspondence to attribute grammars if the programs are viewed as attributes. The correspondence is summarized in the following theorem.

Theorem 4. *Any algorithm on a decomposable structure expressible in the LUO system can be rewritten as an attribute grammar representing the same complexity problem.*

Proof. Each programming primitive can be mapped to an attribute construction. A program $P(a : A)$ is translated into an attribute $P(A)$ and the complexity function $\tau P(z)$ is equivalent to $A_u(z,u)|_{u=1}$, where the variable z marks size and u marks attribute P. Thus, an equivalent system can be obtained and anything solvable in LUO, will be solvable by the same methods. It remains to create the map from programming primitives to attribute constructors.

A program consists of a sequence of sub-programs. Its total complexity is the sum of the complexities of the sub-programs. Thus, if attribute $P(A)$ is the value of the complexity for program P acting on structure A, clearly the attribute is a sum of the attribute values of the sub-programs. It remains to consider each single primitive.

The input are decomposable structures. The remaining primitives depend heavily on the input structure. If the input is a union of classes, a test on unions primitive distinguishes between the possibilities and sums the value according to the case. This is the same as the attribute for unions.

A partial component descent is encapsulated with the Prod operator for products and a selective attribute in the other cases. The full component iteration, maps to an iterative operator. As in the case of attribute grammars, only sub-programs of substructures can be called within a component descent.

□

```
Partition(L:List, L1:List, L2:List)
sets L1 to the list of elts of L< L[1]
sets L2 to the list of elts of L> L[1]
sets L1, L2 to L if |L| = 0
if |L| = 0 then
  L1 = L; L2 = L;
L[0] = 0; L[|L| + 1] = −∞;
i = 2; j = |L|;
l = L[1];
repeat
  repeat i = i + 1 until L[i] > l;
  repeat j = j − 1 until L[j] < l;
  if i < j exchange(L[i], L[j]);
until j < i;
L1 = L[2..j]; L2 = L[i..|L|];
end;
```

```
Quicksort(L:List)
return a sorted copy of L
if |L| <= 1 return L;
otherwise
  Partition(L, L1, L2);
return( Quicksort(L1), L[1], Quicksort(L2));
end;
```

FIGURE 2. Quicksort Algorithm

5.3. **Example: Differentiation.** The analysis of differentiation illustrates the inclusion of LUO in attribute grammars.

Consider regular algebraic expressions composed of constants 0 and 1 and x using the two binary operations + and * and the unary operation exponentiation, that is, $x \mapsto e^x$. The grammar of this set of expressions Exp with Atoms $+, *, e$ is easily described. At the same time we can define the attribute D, the size of the resulting expressions when differentiated.

$$\begin{array}{ll} Exp = 0|1|x|P|T|E & D(Exp) = 1|1|1|D(P)|D(T)|D(E) \\ P = Exp \cdot + \cdot Exp & D(P) = D(Exp) + 1 + D(Exp) \\ T = Exp \cdot * \cdot Exp & D(T) = 3 + D(Exp) + \text{ size}(Exp) + D(Exp) + \text{ size}(Exp) \\ E = e \cdot Exp & D(E) = 2 + D(Exp) + \text{ size}(Exp) \end{array}$$

The attribute `size` refers to the structure size.

The resulting generating function equation set can be manipulated, and using the same Maple tools described in the previous example. We can determine the asymptotic average length of an expression of length n after differentiation $.8042175440\, n^{(3/2)} + \mathrm{O}(n)$. The asymptotic variance is also computable, $0.0394740311\, n^3 + O\left(1.0\, n^{5/2}\right)$

5.4. **Comparison.** LUO remains the more natural way to express some programming primitives such as direct structure descent and declarations with more than one input. It is not as straightforward with attribute grammars to develop a corresponding shorthand notation, consequently the grammars must be manipulated by the user. These manipulations are always possible, since similar manipulations are done internally within the implementation of LUO. However, for other types expressions the attribute description can be much simpler, and the general method simpler.

This implementation of attribute grammars considers each attribute/structure combination, even though in the LUO model a given function may only have one relevant structure input type. This can lead to multivariate functions which need to be manually reduced to be solved and manipulated.

The principle, and significant, advantage to the use of attribute grammars is the additional information. Variance and further moments can be extracted from the equations, unlike the LUO counterparts.



FIGURE 3. The binary search tree and increasing tree associated with [521634]

6. Quicksort

Quicksort is an extremely efficient method of sorting lists indexed by unique keys. There exists substantial analysis on its complexity and of the complexity of several variants, summarized nicely by P. Hennequin [7, 8]. This example illustrates how the type of problem it represents can be modelled with decomposable structures. It also illustrates the incorporation of a new constructor. Figure 2 gives the pseudocode for the Quicksort algorithm.

The following assumptions are made:

- distribution of the input is uniformly random
- the complexity is the total number of comparisons.

Under these conditions, a random instance of the algorithm corresponds to taking as input a random permutation. A run can be visualized with a binary search tree; the permutation is inserted in order into the binary tree in order and then each parent in the tree corresponds to a pivot. The left side of figure 3 illustrates this process on [521634]. In this view, the distance from the root gives the number of times that number has been compared to others. That is, the internal pathlength gives the number of comparisons in total for the run represented by a given tree. Now binary trees are a decomposable structure as they have been defined thus far but they are not sufficient as a class to represent all instances. For example, the inputs 231 and 213 yield the same binary search tree. To remedy this problem, retain the shape of the search tree but label it instead with the order in which the nodes are filled. This eliminates the problem and creates a bijection. To reclaim the original permutation, parse the tree in infix order. If i is encountered at step j, there is a j at position i in the permutation. This resulting structure is a binary tree where the label at each node is less than the label of any ancestor, an *increasing tree*, or *heap*. To describe this with decomposable structures a new operator is required.

6.1. Min Label.

Theorem 3 suggests that given an operator on decomposable structures, if the corresponding generating functions transformations are known, the linear attribute grammar generating function equations are determinable as well. D. Greene introduced a minimum label, or box operator in his thesis on decomposable structures [6]. In a labelled product one designates a particular component of the product as one to receive the smallest label. A sample construction looks like:

$$A = B \cdot Min(C) \cdot D \cdot E.$$

A structure of type A is labelled with its smallest label occurring in the second component. Greene also determined the generating function relationship:

$$A(z) = \int_0^z B(x) \frac{\partial C(x)}{\partial x} D(x) E(x) dx.$$

Having this, the minimum label operator (and similarly a maximum label operator) can be incorporated into the grammar vocabulary. Increasing binary trees can then be described as

$$H = \epsilon \mid \min(Z) \cdot H \cdot H,$$

since a label on a node of subtree must be less than its root.

6.2. **Analysis.** Given the structure, the analysis comes as a result of determining the average path-length on the structures.

Define $H = \epsilon \mid \min(Z) \cdot H \cdot H$, and $\mathrm{ipl}(H) = 0 \mid \mathrm{ipl}(IT) + \mathrm{size}(IT) + \mathrm{ipl}(IT) + \mathrm{size}(IT)$. This yields the system: $H(z,u) = 1 + \int \left(\frac{\partial}{\partial z} z\right) (H(zu,u))^2 \, dz$ which is solved: $H(z) = \frac{1}{1-z}$ and has

$$\frac{[z^n]H_u(z,u)|_{u=1}}{[z^n]H(z)} = 2H_n - 3 + \frac{H_n}{n}$$

where H_n is the n^{th} harmonic number.

This technique can be used to handle variants of Quicksort, relatives of Quicksort such as quick-select, and other problems on increasing trees.

7. Conclusion

Attribute grammars provide a succinct way of describing recursive properties of decomposable structures. The structure yields information as readily as the form of the objects themselves.

The implementation described here takes the definition of decomposible structures and presents a means to define properties. It remains to fully integrate the min operator and selective attributes into the combstruct package. The tools that do exist could constitute a start towards tools for further parameter analysis, such as distribution. Random generation for object grammars is implemented in the qALGO package of Dutour. A similar random generation package could be implemented for decomposible structures.

From the aspect of attribute grammar research, some theory has been developed on the idea of coupling grammars. This simulates repeated application of a function. This, for example, would allow a simple analysis of repeated differentiation, and other composed functions. This requires a system where the attributes may be more than constants, but rather structures.

Finally, a closer look at the results of Duchon may reveal some other possible extensions in this theory.

8. Acknowledgements

The author would like to thank B. Salvy for suggesting this problem and for his comments and help.

References

[1] M. P. Delest and P. Duchon. Exploration de paramètres inconnus par des q-grammaires. In *SCFA '99, Barcelona*, 1999.

[2] M. P. Delest and J.-M. Fédou. Attribute grammars are useful for combinatorics. *Theoretical Computer Science*, 98:65–76, 1992.

[3] I. Dutour and J.-M. Fédou. Object grammars and random generation. *Discrete Mathematics and Theoretical Computer Science*, 2:49–63, 1998.

[4] P. Flajolet, B. Salvy, and P. Zimmermann. Lambda-Upsilon-Omega: The 1989 Cookbook. Research Report 1073, Institut National de Recherche en Informatique et en Automatique, August 1989. 116 pages.

[5] P. Flajolet, B. Salvy, and P. Zimmermann. Automatic average-case analysis of algorithms. *Theoretical Computer Science, Series A*, 79(1):37–109, February 1991.

[6] D. Green. *Formal Languages and their Uses.* Ph. D. thesis, Stanford University, 1985.

[7] P. Hennequin. Combinatorial analysis of quicksort algorithm. *RAIRO Inform. Théor. Appl.*, 23(3):317–333, 1989.

[8] P. Hennequin. *Analyse en moyenne d'algorithmes, tri rapide et arbres de recherche.* Ph. D. thesis, École Polytechnique Palaiseau, 1991.

[9] D. E. Knuth. Semantics of context-free languages. *Mathematical Systems Theory*, 2(2):127–145, 1968.

[10] P. Zimmerman. *Series génératrices et analyse automatique d'algorithmes.* Ph. D. thesis, École Polytechnique Palaiseau, 1991.

E-mail address: mishna@math.uqam.ca

current address: LaCIM, UQÀM, Case Postale 8888, succursale Centre-ville Montréal (Québec) H3C 3P8